



EN 10025-2: 2004 Grade S275JR + AR												Service capability
width x length (mm)	Gauge (mm)											
	8	10	12.5	15	20	25	30	35	40	45	50	
4,000 x 2,000	*	*	*	*	*	*	*	*	*	*	*	Loads up to a maximum of 29 tonnes
5,000 x 2,500	*	*	*	*	*	*	*	*	*	*	*	Loads consisting of mixed sizes and grades available
6,000 x 3,000	*	*	*	*	*	*	*	*	*	*	*	All orders backed by Corus technical advice and support
8,000 x 2,000	*	*	*	*	*	*	*	*	*	*	*	
10,000 x 2,500	*	*	*	*	*	*	*	*	*	*	*	Delivery: Ex stock
12,000 x 3,000		*	*	*	*	*	*					

EN 10025-2: 2004 Grade S355J2+N												Ordering details
width x length (mm)	Gauge (mm)											
	10	12.5	15	20	25	30	35	40	45	50		
4,000 x 2,000	*	*	*	*	*	*	*	*	*	*	*	Orders to be placed directly with your account manager/supervisor or through plate sales in Scunthorpe on 01724 405386
5,000 x 2,500	*	*	*	*	*	*	*	*	*	*	*	
6,000 x 3,000	*	*	*	*	*	*	*	*	*	*	*	Delivery to be agreed at time of order placement.
10,000 x 2,500	*	*	*	*	*	*	*	*	*	*	*	
12,000 x 3,000	*	*	*	*	*	*						An order number and booking reference will be required at time of order placement

Contact details:

Corus Construction and Industrial
 PO Box 1, Brigg Road,
 Scunthorpe
 DN16 1BP

tel:+44 (0) 1724 404040
 fax:+44 (0) 203 107 0870

Technical specifications

Material is certified to EN 10025-2: 2004 Grade S275JR+AR or S355J2+N
 Dimensional tolerances will comply with EN10029:1991
 Surface standard will comply with EN10163

Offered subject to availability at time of order